

# METHOD AND APPARATUS FOR CONTROLLING REMOTE CLIENT COMPUTER

## Field of the Invention

5 The present invention relates to a method and apparatus for controlling a remote client computer; and, more particularly, to a method and apparatus for controlling a remote client computer in which a server controls a client computer performing download and installation of a remote control program, in response to a request signal from the client computer, or one of client computers is set as a server and the other is set as a client through a repeating server managing information about the client computers, and then the server controls the client.

## Description of the Prior Art

10 In remote control methods referred to as "PC anywhere" and "Dr. A/S", a user should know Internet protocol (IP) address of a counterpart to which the user wants to connect. In particular, in order to perform the remote control through a telephone  
20 circuit, the user should confirm and inform to another computer to which the user wants to connect, its IP address.

## Summary of the Invention

25 Therefore, it is an object of the present invention to provide a method and apparatus for controlling a remote client computer in which a server controls a client computer performing download and installation of a remote control program, in

response to a request signal from the client computer, or one of client computers is set as a server and the other is set as a client through a repeating server managing information about the client computers, and then the server controls the client.

5        In accordance with an aspect of the present invention, there is provided a method for performing a remote control of a client computer, which is applied to a remote control system, comprising the steps of: a) at a remote control server, providing a remote control program to the client computer; b) at the remote control server, allowing the client computer to connect to the remote server based on a user identification and a password of the client computer received from the client computer; and c) at the remote control server, performing the remote control of the client computer after discussing contents of the remote control through a chatting unit.

10        In accordance with another aspect of the present invention, there is provided a remote control system for controlling a remote client computer, wherein the client computer is connected to a remote control server through a network, the remote control  
20 server comprising: a system monitoring unit for monitoring change on a display of the remote control server; a bitmap processing unit for generating a bitmap image based on a coordinates value of the change; a data compressing unit for compressing the bitmap image, thereby generating a compressed  
25 bitmap image; a data transmitting/receiving unit for receiving the compressed bitmap image from the data compressing unit and

transmitting the compressed bitmap image to the client computer;  
an event processing unit for transmitting a keyboard/mouse event  
generated in the server to the data transmitting/receiving unit;  
a file transmitting unit for transmitting files necessary for  
5 the remote control of the client computer to data  
transmitting/receiving unit; and a chatting unit for  
transmitting control data to the client computer in the data  
transmitting/receiving unit.

In accordance with further another aspect of the present  
invention, there is provided a computer readable recording  
medium storing instructions for executing a method for  
performing a remote control of a client computer, which is  
applied to a remote control system, comprising the steps of: a)  
at a remote control server, providing a remote control program  
to the client computer; b) at the remote control server,  
15 allowing the client computer to connect to the remote server  
based on a user identification and a password of the client  
computer received from the client computer; and c) at the remote  
control server, performing the remote control of the client  
20 computer after discussing contents of the remote control through  
a chatting unit.

In accordance with still further another aspect of the  
present invention, there is provided a method for performing a  
remote control of client computers, which is applied to a remote  
control system, comprising the steps of: a) at a repeating  
25 server, providing a remote control program to a first and a

second client computers; b) at the repeating server, determining whether the first and the second client computers are registered users based on based on user identifications and passwords received from the first and the second client computers, and  
5 allowing the first and the second client computers to enter a waiting room of a chatting unit; c) at the repeating server, informing the first client computer of an Internet protocol address of the second client computer; and d) at the first client, performing the remote control of the second client computer.

In accordance with still further another aspect of the present invention, there is provided a computer readable recording medium storing instructions for executing a method for performing a remote control of client computers, which is applied to a remote control system, comprising the steps of: a) at a repeating server, providing a remote control program to a first and a second client computers; b) at the repeating server, determining whether the first and the second client computers are registered users based on based on user identifications and  
20 passwords received from the first and the second client computers, and allowing the first and the second client computers to enter a waiting room of a chatting unit; c) at the repeating server, informing the first client computer of an Internet protocol address of the second client computer; and d)  
25 at the first client, performing the remote control of the second client computer.

## Brief Description of the Drawings

Other objects and aspects of the invention will become apparent from the following description of the embodiments with reference to the accompanying drawings, in which:

Fig. 1 is a block diagram of a remote control system in accordance with one embodiment of the present invention;

Fig. 2 is a detail diagram of a remote control server in Fig. 1;

Fig. 3 is a flow chart illustrating a remote control method in accordance with one embodiment of the present invention;

Fig. 4 is a detail flow chart showing a remote control process in Fig. 3;

Fig. 5 is a block diagram of a remote control system in accordance with another embodiment of the present invention;

Fig. 6 is a detail block diagram of a repeating server in Fig. 5; and

Fig. 7 is a flow chart illustrating a remote control method in accordance with another embodiment of the present invention.

## Preferred Embodiments of the Invention

Hereinafter, embodiments of the present invention will be described in detail referring to the accompanying drawings.

Fig. 1 is a block diagram of a remote control system in accordance with one embodiment of the present invention, to which a remote control method is applied.

Referring to Fig. 1, a remote control system includes a remote control server 10, a network 20 and at least a client computer.

The remote control server 10 controls the remote client computer 30 based on a request signal from the remote client computer 30. The client computer 30 downloads and installs a program for the remote control (hereinafter, which is referred to as "a remote control program") and then is controlled by the remote control server 10.

Fig. 2 is a detail diagram of a remote control server in Fig. 1.

Referring to Fig. 2, the remote control server 10 includes a system monitoring unit 11, a bitmap processing unit 12, a data compressing unit 13, a data transmitting/receiving unit 14, an event processing unit 15, a file transmitting unit 16 and a chatting unit 17.

The system monitoring unit 11 monitors a change on a display unit (not illustrated) of the remote control server. The bitmap processing unit 12 receives a coordinates value of the change and generates a bitmap image. The data compressing unit 13 receives from the bitmap processing unit 12 and compresses the bitmap image. The data transmitting/receiving unit 14 transmits the compressed bitmap image to the client computer 30 through the network 20. The event processing unit 15 transmits a keyboard/mouse event generated in the remote control server to the data transmitting/receiving unit 14. The file transmitting

unit 16 extracts files necessary for controlling the client computer 30 and transmits extracted files to the data transmitting/receiving unit 14. The chatting unit 17 transmits/receives information for the remote control to/from the user of the client computer 30.

Fig. 3 is a flow chart illustrating a remote control method in accordance with one embodiment of the present invention.

First, the client computer 30 downloads and installs a remote control program at step 100, and receives a user identification (ID) and a password from the user at step 120. When the client computer 30 is connected to the remote control server 10 at step 140, the remote control server 10 discusses contents to be controlled with the user of the client computer, and then performs a remote control process at step 180.

Fig. 4 is a detail flow chart showing a remote control process in Fig. 3.

A change on a display of the remote control server is monitored by the system monitoring unit 11 at step 181. When coordinates value of the change is transmitted to the bitmap processing unit 12, a bitmap image is generated at step 182. The bitmap image is transmitted from the bitmap processing unit 12 to the data compressing unit 13 at step 183, the bitmap image is compressed and transmitted to the data transmitting/receiving unit 14 at step 184. The event processing unit 15 transmits a keyboard/mouse event generated in the remote control server to the data transmitting/receiving unit 14 at step 185. The file

transmitting unit 16 extracts files necessary for the remote control of the client computer 30 and transmits extracted files to the data transmitting/receiving unit 14 at step 186. Control data, i.e., the compressed bitmap image, the keyboard/mouse event, the files necessary for the remote control are transmitted to the client computer 30 through the network at step 187, and the remote control process is completed by the client computer's processing the received control data at step 188.

Hereinafter, a second embodiment of the present invention will be described in detail referring to Figs. 5 through 7.

Fig. 5 is a block diagram of a remote control system in accordance with another embodiment of the present invention, to which a remote control method is applied.

Referring to Fig. 5, a remote control system includes a network 20, a repeating server 220 and client computers 230 and 240. The repeating server 220 manages user information, e.g., an Internet protocol (IP) address, a user identification (ID) and a password of each user and provides a room for conversation about the remote control, which is referred to as "a conversation room". The client computers, a first client and a second client, download a remote control program from the repeating server 220, install it and then perform a connection to the repeating server 220. The client computers select one of them as a server and the other as a client to be controlled by the server.



Fig. 6 is a detail block diagram of a repeating server to which a remote control method in accordance with the present invention is applied.

Referring to Fig. 6, the repeating server 220 includes a repeating server connecting unit 221, a user authenticating unit 222, a user database 223 and a repeating chatting unit 224.

The repeating server connecting unit 221 receives user data. The user authenticating unit 222 authenticates the user based on user information stored on a user database 223 corresponding to the user data from the repeating server connecting unit 221, e.g., a user ID and a password. The repeating chatting unit 224 transmits and receives information necessary for the remote control to/from the client computers and determines which one of the client computers is to be a server to perform the remote control.

Fig. 7 is a flow chart illustrating a remote control method in accordance with another embodiment of the present invention.

The first and the second client computers download and install a remote control program after connecting to the repeating server 220 at step 300. If the user data, e.g., the user ID and the password are inputted at step 302, the user authenticating unit 222 of the repeating server 220 retrieves the user information based on the user ID and the password from the user database 223 and determines whether the user trying to connect is registered or not at step 304.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

If the user is a rightful registered user, the first and the second client computers 230 and 240 can be entered to a waiting room of the chatting unit at step 306. If not, the process is returned to the step 300 to download/install the remote control program.

The first and the second client computers 230 and 240 enter a conversation room wanted to be entered at step 308. The first client computer 230 selects a user ID of the client computers with which the first client wants to talk at step 310. Then, the repeating server determines whether the selected client computer is connected or not at step 312.

If the selected client computer is not connected, the process repeats the step 310 to select a user ID. If so, the first client computer transmits a connection request data at step 314, and determines whether a connection is allowed or not at step 316. Hereinafter, for easy description, a user, which wants to be connected, is referred to a second client computer 240. If the connection is allowed, the repeating server 220 transmits an IP address of the second client computer to the first client computer and performs the connection for the remote control at step 318, then the first client computer 230 performs a remote control process of the second client computer at step 320. In other words, the first client computer 230 is the subject of the remote control and the second client computer 240 is the object of the remote control.

The remote control process at step 320 is similar with the remote control process mentioned above with reference to Fig. 4 except that the subject of the remote control is not a remote control server but the first client computer and the object of the remote control is the second client computer 240. Therefore, for only easy description, detailed description about the remote control process will be skipped.

In the remote control system in accordance with the present invention, the remote control server performs the remote control based on the connection request signal received from the client computer performing download/install of the remote control, or performs the remote control through the repeating server managing the user information of the client computers. Therefore, using the present invention, processes for the connection can be effectively reduced. Even if there is no remote control server, the remote control can be performed.

Although the preferred embodiments of the invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.